

**Thank you for purchasing a Mustard Bikes Fender Eliminator.  
The following is a brief guide for installation of your  
Honda CB650F Fender Eliminator.**

1. Remove rider seat from bike.
2. Unplug the 3, 2 wire plugs leading to the fender from underneath the rider's seat.
3. Remove 3 x bolts (5mm allen) holding the stock fender.
4. Remove the stock fender gently feeding through the wires until the fender is removed.
5. If using after market indicators continue from point 11.
6. Remove 5 x phillips screws from fender extension and remove extension from fender.
7. Remove 2 x phillips screws from fender and spread fender apart with a flat blade screw driver.
8. Remove 1 x phillips screw on the back of each indicator.
9. Remove indicator locks and rubbers and indicators from fender.
10. Fit indicators to fender eliminator after fitting supplied spacers (Oval rings) to rubbers.
11. Fit OEM number plate light plug to the LED bolt. The LED bolt is polarity sensitive.
12. Plug in LED bolt and check operation. If it does not light up switch the two wires.
13. Feed 20mm M6 bolt (supplied) from under seat into the rear most mounting hole in the undertail.
14. Fit 8mm M6 nut (supplied) to 20mm bolt and tighten.
15. Feed wires through undertail and position fender eliminator in place.
16. Use 2 x M6 nut (supplied) to fix fender eliminator from under riders seat.
17. Use 1 x M6 nut (supplied) to fix fender eliminator from the underside of the bikes tail.
18. Refit rider's seat and check all lights for correct operation.

If you have any problems with installation feel free to contact us at [help@mustardbikes.com](mailto:help@mustardbikes.com) for any queries.

