



2008 Kawasaki Ninja 250 Fender Eliminator Install guide.

Thank you for purchasing this quality product from Mustard Bikes. This product is designed to refine the bulky rear fender on Kawasaki's 2008 onwards Ninja 250.

This Fender Eliminator kit contains a tail light shroud, fender eliminator, 2 bolts and 6 nylock nuts.

The following are some basic instructions to help you install your Fender Eliminator. If you are unfamiliar with your motorcycle it may be necessary to consult a workshop manual.

- 1.** Remove the two side panels underneath the riders seat, the seat itself, the pillion seat and the two rear fairing panels. Consult your workshop manual if unfamiliar with removing these parts.
- 2.** Remove the tail light top cover and unplug all wiring for the rear fender. Undo the four bolts to remove the rear fender from the bike.
- 3.** Place the tail light in the tail light shroud supplied and bolt the tail light, shroud and fender eliminator together using the standard bolts, as they were mounted in the standard fender. Do not tighten these bolts completely.
- 4.** Mount the complete assembly onto the bike. Use the two longer bolts and ny-lock nuts in the most rearward mounting holes. Use two of the standard bolts and ny-lock nuts in the forward two holes.
- 5.** Tighten the tail light bolts in place. Install the indicators (two ny-lock nuts supplied) and route all wiring through the hole in the tail light shroud. Plug in all wiring including the LED tail light on the fender eliminator.

6. Now is a good time to test all lights are operating. The LED bolt is polarity sensitive. If it does not light up swap it's two wires around and it should work.

7. Re-install the tail light top cover. If the tabs of the tail light shroud do not line up they can be lightly bent into place. Check that all brake lights and indicators are operating correctly.

8. Reinstall the two rear fairing panels, pay close attention to making sure the fairings mount correctly and mount flush to the tail light shroud. Excessive force should not be used when re-installing fairings.

9. Reinstall the riders seat, pillion seat and the two side panels below the riders seat. Make a final check that everything is install and working correctly and that all bolts have been correctly tightened.

Congratulations!

If all went well your Mustard Bikes Kawasaki Ninja 250 Fender Eliminator is now installed.

If you have any problems with installation feel free to contact us at help@mustardbikes.com for any queries.

Disclaimer:

This install guide is just that, a guide only. The manufacturer takes no responsibility if you screw up. The manufacturer takes no responsibility for any damage caused to any persons or property through the use of this product.



For more parts visit:

WWW.MUSTARDBIKES.COM