

**Thank you for purchasing a Mustard Bikes Fender Eliminator.
The following is a brief guide for installation of your
12- Kawasaki ER-6 Fender Eliminator.**

1. Remove pillion seat using the key and then remove the rider's seat by sliding seat backwards.
2. Locate indicator wires, follow back to the connectors (right hand side of bike) and unplug from the loom.
3. Undo 3 x 10mm bolts holding up the stock fender.
4. Undo 1 x Philips screw on the underside of the fender and gently remove assembly from the bike.
5. To access the OEM indicators remove 4 x 7mm bolts on underside of stock fender and undo wiring tab.
6. Remove 2 x 8mm bolts holding the fender frame to the plastic guard.
7. Remove the screw, locking plate and fitting plate to remove the stock indicators. Refit to fender eliminator.
8. Offer assembly up to the bike. Wiring should locate in the small cut out of the middle finger of the eliminator.
9. Bolt eliminator in place using supplied ny-lock nuts and 2 of the original bolts.
10. Plug in wiring and check for correct operation. The LED bolt is polarity sensitive. If it does not light up switch the wires around and check again.
11. Refit rider and pillion seats.

Please contact us at help@mustarbikes.com if you have any issues with installation.
We will be more than happy to help in any way we can.

