

**Thank you for purchasing a Mustard Bikes Fender Eliminator.
The following is a brief guide for installation of your
Suzuki GSXS-1000 Fender Eliminator.**

1. Remove pillion seat and rider seat (5mm Allen bolt under center rear of seat) from bike.
2. Locate plate light and indicator cables and follow back alongside right side of tail.
3. Loosen cable ties holding cables in places by depressing the tab and pushing the tail through.
4. Unplug indicator and plate light cables, black grey and white plugs, and feed out to glove box (You may need to rotate the cables around the frame rail to reach the plugs).
5. Undo 4 x 10mm bolts from under fender. Gently remove stock fender from bike.
6. Remove 5 x Philips head screws underneath stock fender and separate the top and bottom parts.
7. Remove stock indicators (8mm nut) and fit to fender eliminator.
8. Fit OEM number plate light plug to the fitted LED bolt. If LED bolt does not light up switch the two wires (LED bolt is polarity sensitive).
9. Fit 2 supplied plastic spacers to the raised thread nuts underneath the bike. The spacers do not have a front or rear and will fit either.
10. Feed cables through the bike and place fender eliminator up to the bike.
11. Bolt fender eliminator to the bike using supplied Allen head bolts.
12. Feed indicator and plate light cables following original routing and re-connect.
13. Test all lights for proper operation.
14. Refit rider's seat and pillion seat.

If you have any problems with installation feel free to contact us at help@mustardbikes.com for any queries.

We will be more than happy to help in any way we can.

