

**Thank you for purchasing a Mustard Bikes Fender Eliminator.
The following is a brief guide for installation of your
Yamaha MT-09 Fender Eliminator.**

1. Remove rider seat from bike.
2. Remove 2 x bolts from each side rear seat cowling (10mm hex socket), 4 in total.
3. Remove 4 x push plugs from underneath the left side seat cowling and remove cowling.
4. Remove 3 x push plugs from underneath the right side seat cowling and remove cowling.
5. Remove the lock plate from sub-frame (4 x 8mm hex socket).
6. Unplug indicator and number plate light plugs (located right hand inside of sub-frame).
7. Remove 4 x nuts (4 x 10mm hex socket) holding stock fender and remove stock fender.
8. Remove 4 x bolts from top side of stock fender (4mm allen) and 4 x Phillips screw from underside.
9. Remove indicators and fit to fender eliminator after fitting supplied spacers (Oval rings).
10. Fit fender eliminator base to bike using 4 x 16 mm bolts and stock nuts.
11. Feed Fender Eliminator wiring through and fit fender eliminator to base using 3 x supplied M6 nuts.
12. Plug in wiring for indicators and number plate light and check for operation.
13. If LED bolt does not light up switch the two wires (LED bolt is polarity sensitive).
14. Refit lock plate to sub-frame (4 x 8mm hex socket).
15. Refit left and right rear cowling panels replacing all push plugs and 4 x bolt (10mm hex socket).
16. Use supplied cap to cover seat lock.
17. Refit rider's seat.

If you have any problems with installation feel free to contact us at help@mustardbikes.com for any queries.
We will be more than happy to help in any way we can.

